

Uplink User Capacity in a CDMA System with Hotspot Microcells: Effects of Finite Transmit Power and Dispersion

Shaline Kishore, Larry J. Greenstein, H. Vincent Poor, Stuart C. Schwartz

Abstract—This paper examines the uplink user capacity in a two-tier code division multiple access (CDMA) system with hotspot microcells when user terminal power is limited and the wireless channel is *finitely-dispersive*. A finitely-dispersive channel causes variable fading of the signal power at the output of the RAKE receiver. First, a two-cell system composed of one macrocell and one embedded microcell is studied and analytical methods are developed to estimate the user capacity as a function of a dimensionless parameter that depends on the transmit power constraint and cell radius. Next, novel analytical methods are developed to study the effect of variable fading, both with and without transmit power constraints. Finally, the analytical methods are extended to estimate uplink user capacity for *multicell* CDMA systems, composed of multiple macrocells and multiple embedded microcells. In all cases, the analysis-based estimates are compared with and confirmed by simulation results.

Index Terms— Cellular systems, code division multiple access, microcells.

I. INTRODUCTION

Wireless operators often install low-power *hotspot microcell* base stations to provide coverage to small high-traffic regions within a larger coverage area. These microcells enhance the user capacity and coverage area supported by the existing high-power *macrocell* base stations. In this paper, we study these gains for a *two-tier code division multiple access (CDMA) network* in which both the macrocells and microcells use the same set of frequencies. Specifically, we study the effects, on the uplink capacity and coverage area, of transmit power constraints and variable power fading due to multipath.

Earlier studies have examined the uplink performance of these single-frequency, two-tier CDMA systems, e.g., [1]–[6]. In [4], we showed how to compute the uplink user capacity for a single-macrocell/single-microcell (two-cell) system using exact and approximate analytical methods that accounted for random user locations, propagation effects, signal-to-interference-plus-noise ratio (SINR)-based power control, and various methods of base station selection. In [5],

we calculated capacity gains under similar assumptions for a system composed of multiple macrocells and/or multiple microcells; the results pointed to a roughly linear growth in capacity as the number of these base stations increase, where the constants of the linear curve were derivable solely from the analysis for the two-cell case. This linear approximation was conjectured based on the trends observed from several simulations. More recently, we have developed an *analytical* approximation to the user capacity of a multicell system which is much tighter than the empirical result of [5]; and is valid over a larger number of embedded microcells. Interestingly, this new analytical approach also depends on constants obtained from a far-simpler two-cell analysis. These studies therefore highlight the importance of understanding two-cell performance in computing the performance of larger multicell systems.

The capacity gains demonstrated in these earlier works were based on assumptions that 1) user terminals have unlimited power; and 2) that the wireless channel is so wideband that user signals have constant output power after RAKE receiver processing. This latter condition is equivalent to assuming that user signals go through an infinitely-dispersive channel before reception.¹ In this paper, we remove these conditions. Portions of this work were presented in [7] and a companion paper on *downlink* capacity [8] showed that this type of system is uplink-limited. Here, we improve the presentation in [7] and present several new results. Specifically, we show how the capacity/coverage tradeoff under finite power constraints can vary significantly with shadow fading. Further, we bridge our study of finite power constraints and finite channel dispersion by presenting a new analysis of user capacity in two-cell systems under *both* maximum transmit power constraints and variable power fading. Finally and most significantly, we develop and verify analytical expressions for the total user capacity of *multicell* two-tier CDMA systems under finite dispersion.

Section II describes the basic two-cell system and the model used to capture the power gain between a user and a base; and it summarizes our previous results for total uplink capacity. Section III assumes a limit on terminal transmit

S. Kishore is with the Department of Electrical and Computer Engineering, Lehigh University, Bethlehem, PA, USA. L.J. Greenstein is with WINLAB, Rutgers University, Piscataway, NJ, USA. H.V. Poor and S.C. Schwartz are with the Department of Electrical Engineering, Princeton University, Princeton, NJ, USA. This research was jointly supported by the New Jersey Commission on Science and Technology, the National Science Foundation under CAREER Grant CCF-03-46945, Grant ANI-03-38807, and the AT&T Labs Fellowship Program. Contact: skishore@eecs.lehigh.edu.

¹By “infinitely dispersive,” we mean that the channel has an infinitude of significant paths so that, after RAKE processing, the receiver signal output has constant power.

power and approximates total capacity as a function of this power and cell size. Section IV relaxes the condition on infinite dispersion and approximates the total capacity, for both limited and unlimited terminal power, as a function of the multipath delay profile. Section V extends the results for finite dispersion and unlimited terminal power to the case of multiple macrocells and multiple microcells. Simulations confirm the accuracy of the approximation methods over a wide range of practical conditions and assumptions.

II. SYSTEM AND CHANNEL DESCRIPTION

The System: We first consider a system with a macrocell and an embedded microcell which together contain N total users, comprising N_M in the macrocell and $N_\mu = N - N_M$ in the microcell. We assume users have random codes of length W/R , where W is the system bandwidth and R is the user rate. Each user is power-controlled by its base so as to achieve a required uplink power level. It was shown in [4] that the required received power levels to meet a minimum SINR requirement of Γ are

$$S_M = \eta W \frac{K - N_\mu + I_M}{(K - N_\mu)(K - N_M) - I_M I_\mu} \quad (1)$$

and

$$S_\mu = \eta W \frac{K - N_M + I_\mu}{(K - N_\mu)(K - N_M) - I_M I_\mu} \quad (2)$$

at the macrocell and microcell base stations, respectively. Here, $K = 1 + (W/R)/\Gamma$ denotes the single-cell pole capacity [9], η is the power spectral density of the additive white Gaussian noise, and I_M and I_μ are *normalized cross-tier interference* terms. Specifically, $S_\mu I_M$ is the total interference power at the macrocell due to microcell users and $S_M I_\mu$ is the total interference power at the microcell due to macrocell users. Thus,

$$I_M = \sum_{j \in U_\mu} \frac{T_{Mj}}{T_{\mu j}}; \quad I_\mu = \sum_{j \in U_M} \frac{T_{\mu j}}{T_{Mj}}, \quad (3)$$

where U_μ represents the set of microcell users, U_M represents the set of macrocell users, and T_{Mk} and $T_{\mu k}$ are the path gains from user k to the macrocell and microcell base stations, respectively. We say that a given arrangement of user locations and path gains is *feasible* if and only if the common denominator in (1) and (2) is positive. The fraction of all possible cases (i.e., all combinations of I_M and I_μ) for which this occurs is called the *probability of feasibility*. The cross-tier interference terms depend on the path gains for all users to both base stations and on the method by which users select base stations, leading to the sets U_μ and U_M .

Path Gain Model: We model the instantaneous power gain (i.e., the sum of the power gains of the resolvable multipaths) between user k and base station l as

$$T_{lk} = \begin{cases} H_l \left(\frac{b_l}{d_{lk}} \right)^2 10^{\zeta/10} \rho & d_{lk} < b_l \\ H_l \left(\frac{b_l}{d_{lk}} \right)^4 10^{\zeta/10} \rho & d_{lk} \geq b_l \end{cases}, \quad (4)$$

where d_{lk} is the distance between user k and base station l ; b_l is the breakpoint distance of base station l at which the slope of the decibel path gain versus distance changes; H_l is a gain factor that captures the effects of antenna height and gain at base station l ; $10^{\zeta/10}$ represents *shadow fading*; and ρ is the variable fading due to multipath [10]–[11]. Note that ζ and ρ are different for each user-base pair (l, k) but, for convenience, we suppress the subscripts for these terms. Since the antenna height and gain are greater at the macrocell, we can assume $H_M > H_\mu$. We model ζ as a zero mean Gaussian random variable with variance σ_l^2 for base station l . The fading due to multipath, ρ , is scaled to be a unit-mean random variable ($E\{\rho\} = 1$). In an infinitely dispersive channel, $\rho = 1$. Let $\tilde{T}_{lk}$ denote the path gain between user k and base l in an infinitely dispersive channel. Thus, $\tilde{T}_{lk}$ represents the local spatial average of T_{lk} , and $T_{lk} = \tilde{T}_{lk}\rho$.

Base-Selection Scheme: We assume a user k chooses to communicate with the macrocell base station if $\tilde{T}_{Mk}$ exceeds $\tilde{T}_{\mu k}$ by a fraction δ , called the *desensitivity* parameter. Thus, in both finitely-dispersive and infinitely dispersive channels, the user selects base stations according to the local mean path gains.² With no loss in generality, we assume $\delta = 1$ in this study.

Capacity: The path gain model and the selection scheme described above imply that the cross-tier interference terms are random variables; they depend on the random variations due to shadow and multipath fading and on the random user locations. In [4], we demonstrated how to compute the cumulative distribution functions (CDF's) of the two cross-tier interference terms in (3) under the condition of infinite dispersion. Let $\tilde{I}_M$ and $\tilde{I}_\mu$ denote these cross-tier terms under that condition. The CDF's of $\tilde{I}_M$ and $\tilde{I}_\mu$ were used to compute the exact uplink user capacity in a two-cell system with unlimited terminal power. In addition, the mean values of $\tilde{I}_M$ and $\tilde{I}_\mu$ were used to reliably approximate attainable user capacity for the two-cell system as

$$\tilde{N} = \frac{2K}{1 + \sqrt{\tilde{v}_M \tilde{v}_\mu}}, \quad (5)$$

where $\tilde{v}_M$ and $\tilde{v}_\mu$ are the mean values (over all user locations and shadowing fadings) of single terms in the sums $\tilde{I}_M$ and $\tilde{I}_\mu$, respectively.³ The total user capacity of the two-cell system thus depends on K (a system parameter) and the product $\tilde{v}_M \tilde{v}_\mu$. We computed this product under various conditions and observed that it (and therefore $\tilde{N}$) are robust to variations in propagation parameters, separation between the two base stations, and user distribution. Its value under all conditions examined was about 0.09, leading to the robust result $\tilde{N} \approx 1.5K$.

²In [4], we studied this path gain-based selection method as well as the selection scheme in which users are assigned to base stations such that each terminal requires the least transmit power. The result show that the latter scheme out-performs the path-gain-based method by roughly 15% in capacity.

³In computing $\tilde{N}$, we used the fact, proved in [5], that maximal total capacity results when $N_M = N_\mu$.

III. USER CAPACITY WITH LIMITED TERMINAL POWER

A. Analysis

In this section, we assume an infinitely dispersive channel and study a system where each user terminal has a maximum transmit power constraint of $P_{\max}$. The two-cell system is unable to support a given set of N users if the users are *infeasible* (i.e., unsupportable even with unlimited terminal power) or if any one of the N users requires a transmit power higher than $P_{\max}$. We have already computed the probability of infeasibility of N total users in [4]; we now determine the probability that any one of N feasible users exceeds the terminal power limit of $P_{\max}$. The combined event, when the system is either infeasible or feasible but a user terminal exceeds the transmit power requirements, is referred to as *outage*. The probability of outage for N users can then be written as

$$P_{out}(N) = P_{inf}(N) + (1 - P_{inf}(N)) \cdot \Pr [P > P_{\max} | N], \quad (6)$$

where $P_{inf}(N)$ is the probability of infeasibility of N users and $\Pr [P > P_{\max} | N]$ is the probability that the transmit power of any one of the N feasible users exceeds $P_{\max}$. We seek the values of N that a two-cell system can support for a specified probability of outage, i.e., we desire the largest N such that $P_{out}(N) \leq \alpha_{out}$.

We assume $b_M = b_\mu = b$. For analytical purposes, it is convenient to write the path gain between user k and base station l as:

$$\tilde{T}_{lk} = H_l \left(\frac{b}{d_{\max}} \right)^4 \tilde{T}'_{lk}, \quad (7)$$

where $d_{\max}$ is the desired maximum distance from the macrocell base station to a system user (it can be regarded as the macrocell radius), and

$$\tilde{T}'_{lk} = \begin{cases} \left(\frac{d_{\max}}{d_{lk}} \right)^2 \left(\frac{d_{\max}}{b} \right)^2 10^{\zeta/10}, & d_{lk} < b \\ \left(\frac{d_{\max}}{d_{lk}} \right)^4 10^{\zeta/10}, & d_{lk} \geq b \end{cases}. \quad (8)$$

Microcell user j transmits at power $P = S_{\mu j} / \tilde{T}_{\mu j}$; thus P exceeds $P_{\max}$ if

$$\frac{\tilde{S}'_\mu}{\tilde{T}'_{\mu j}} > \frac{P_{\max} H_\mu}{\eta W} \left(\frac{b}{d_{\max}} \right)^4 \equiv F \quad (9)$$

where $\tilde{S}'_\mu = S_\mu / \eta W$. Similarly, the required transmit power of macrocell user i exceeds $P_{\max}$ if

$$\frac{\tilde{S}'_M}{\tilde{T}'_{Mi}} > \frac{P_{\max} H_M}{\eta W} \left(\frac{b}{d_{\max}} \right)^4 = FH, \quad (10)$$

where $\tilde{S}'_M = S_M / \eta W$ and $H = H_M / H_\mu$.

Note that $\tilde{S}'_M$ and $\tilde{S}'_\mu$ and all path gains are random variables, related to the randomness of user locations and shadow fading. Following the steps outlined in [4] to obtain the probability distributions of $\tilde{I}'_M$ and $\tilde{I}'_\mu$, we can extend the analysis to compute the distributions of $\tilde{S}'_M$ and $\tilde{S}'_\mu$. Next, we can determine the distributions of $\tilde{T}'_M$ and $\tilde{T}'_\mu$ for a random macrocell user and a random microcell user, respectively.

With the distributions of $\tilde{S}'_M$, $\tilde{S}'_\mu$, $\tilde{T}'_M$ and $\tilde{T}'_\mu$, we can then determine $\Pr [P > P_{\max} | N]$ as a function of F :

$$\Pr [P > P_{\max} | N] = \sum_{n=0}^N \binom{N}{n} p^n q^{N-n} (1 - p_M^n p_\mu^{N-n}), \quad (11)$$

where p is the probability of a user assignment to the macrocell;⁴ $q = 1 - p$;

$$p_M = \Pr [\tilde{S}'_M / \tilde{T}'_M \leq FH]; \quad p_\mu = \Pr [\tilde{S}'_\mu / \tilde{T}'_\mu \leq F]. \quad (12)$$

Finally, we can determine the largest N for which $P_{out}(N) \leq \alpha_{out}$ for a given value of F . However, instead of computing the distributions of $\tilde{S}'_M$ and $\tilde{S}'_\mu$, we propose an approximate method that works quite well, namely, using the means of $\tilde{S}'_M$ and $\tilde{S}'_\mu$. This approach retains (6) and (11) but uses the following modified values for p_M and p_μ :

$$\tilde{p}'_M = \Pr [E \{ \tilde{S}'_M \} / \tilde{T}'_M \leq FH]; \quad (13)$$

$$\tilde{p}'_\mu = \Pr [E \{ \tilde{S}'_\mu \} / \tilde{T}'_\mu \leq F]. \quad (14)$$

This greatly simplifies calculating the probability of outage, with minor loss in accuracy.

B. Numerical Results

We use simulation to study the two-cell system in Figure 1. Specifically, we assume a square geographic region, with sides of length S . At a distance D from the center of this square is a smaller square region, with sides of length s . A portion of the total user population N is uniformly distributed over the larger square region and the remaining users are uniformly distributed over the smaller square region. The smaller square thus represents a traffic hotspot within the larger coverage region. A macrocell base with antenna height h_M is at the center of the larger square, while a microcell base with antenna height h_μ is at the center of the smaller square. We assume each user terminal has antenna height h_m . These antenna heights are used to compute the distance between transmit antenna at each user terminal and the receive antenna at the two base stations. The breakpoint of the path loss to the microcell base is engineered to be $s/2$, to help ensure that the microcells provide strong signals to those users contained within the high density region, and sharply diminishing signals to users outside it. Finally, we assume that on average half of the N users are uniformly distributed over the hotspot region surrounding the microcell base. This is done to obtain a roughly equal number of users for each base, i.e., to ensure that the maximal user capacity occurs with high probability.

Using the parameter values listed in Table 1, we determine the total user capacity that can be sustained with 5% outage probability for various values of $P_{\max}$. Figure 2 shows the resulting user capacity as a function of F as defined in (9). We observe the close correspondence between the approximate and simulation results. We also note that the user capacity goes to an asymptotic value as F gets large and that, below a critical value of F (denoted by F^*), the user

⁴ p can be computed using the methods in [4].




Fig. 1. A two-cell system composed of a larger square region with a smaller square region containing a high-density of users.

capacity decreases sharply as F decreases. (From the figure, $F^* \approx 1$.) In other words, there are critical combinations of $P_{\max}$ and $d_{\max}$ such that, if we either reduce the transmit power constraint or increase the desired coverage area, the overall user capacity noticeably drops; and, for values of $F > F^*$, the system operates as if there is unlimited terminal power.

In an earlier study [12], we found that total user capacity is nearly invariant to σ_M and σ_μ , increasing very slightly as σ_M and σ_μ increase. This finding was for unlimited terminal power. We now consider the uplink user capacity as a function of F for various pairs of (σ_M, σ_μ) . The results, obtained via simulation, are in Figure 3. Even though the capacity for unlimited transmit power (F infinite) is slightly larger for $\sigma_M = 12, \sigma_\mu = 6$ [12], the curves increase much faster for smaller values of σ_M and σ_μ . Thus, although for unlimited transmit power the total user capacity is roughly invariant to σ_M and σ_μ , it can vary significantly with these parameters under transmit power constraints.

IV. USER CAPACITY WITH VARIABLE FADING: TWO-CELL SYSTEM

A. Analysis

We now consider *finite dispersion* (i.e., a finite number of significant multipaths), which causes the sum of the multipath powers to fade with time as a user moves in the environment. We assume that users still select bases according to the *slowly* varying path gains, $\tilde{T}_{lk}$, but the fluctuations of signals and interferences due to multipath lead to instantaneous occurrences of outage.




Fig. 2. Total user capacity as a function of F . Results are for a single macrocell with or without an embedded microcell, with an analytical approximation shown for the former. (Infinitely dispersive channel)




Fig. 3. Total user capacity as a function of F for various combinations of σ_M and σ_μ . (Two-cell two-tier system and infinitely dispersive channel)

1) *Channel Delay Profile*: The instantaneous path gain from base l to user k is $T_{lk} = \rho \tilde{T}_{lk}$, where ρ is independent and identically distributed (i.i.d.) over all (l, k) . Let r_n represent the instantaneous power gain of the n -th multipath component of a particular uplink channel. Then, for that channel,

$$\rho = \sum_{n=1}^{L_p} r_n, \quad (15)$$

where L_p is the total number of multipaths and we assume a scaling such that $E\{\rho\} = 1$. We consider four possible multipath delay profiles, for each of which ρ has a different statistical nature. One is for the so-called *uniform channel*, in which the L_p multipaths are i.i.d. and Rayleigh-fading, i.e., each has a power gain that is exponentially distributed with a

mean of $1/L_p$.

The other three delay profiles studied here are based on cellular channel models for the typical urban (TU), rural area (RA), and hilly terrain (HT) environments provided in third-generation standards. See, for example, [13], which tabulates $E\{r_n\}$ in dB for these environments.

2) *Methodology*: Base selections (and thus, the sets U_μ and U_M) are made according to the local average path gains, $\tilde{T}_{lk}$. The instantaneous cross-tier interference powers are

$$I_M = \sum_{i \in U_\mu} \frac{T_{Mi}}{\tilde{T}_{\mu i}} = \sum_{i \in U_\mu} \frac{\rho_{Mi}}{\rho_{\mu i}} \cdot \frac{\tilde{T}_{Mi}}{\tilde{T}_{\mu i}}; \quad (16)$$

$$I_\mu = \sum_{i \in U_M} \frac{T_{\mu i}}{\tilde{T}_{Mi}} = \sum_{i \in U_M} \frac{\rho_{\mu i}}{\rho_{Mi}} \cdot \frac{\tilde{T}_{\mu i}}{\tilde{T}_{Mi}} \quad (17)$$

where ρ_{Mi} and $\rho_{\mu i}$ are i.i.d. random variables, each distributed as ρ in (15). We see from the definitions of I_M and I_μ that, at any one instant, the system could become infeasible or, more generally, experience outage, depending on the values of ρ_{Mi} and $\rho_{\mu i}$. Here again, we seek the largest number of users, N , that can be supported such that $P_{out}(N) \leq \alpha_{out}$.

The exact method for calculating N requires that the distributions of I_M and I_μ be computed. The procedure is even more complex than before since we must incorporate the effects of the additional random quantities, ρ_{Mi} and $\rho_{\mu i}$. Thus, we resort to two analytical approximations. The first estimates total user capacity under finite dispersion but for large F (i.e., $F > F^*$); and the second estimates capacity under both finite dispersion and finite transmit power requirements.

3) *Total User Capacity for F Large*:

a) *Estimated User Capacity in a Uniform Channel*:

The total user capacity in a uniform channel, N_u , can be approximated by modifying the mean method presented in (5). Specifically, we postulate that

$$N_u = \frac{2K}{1 + \sqrt{\bar{v}_M \bar{v}_\mu}}, \quad (18)$$

where $\bar{v}_M = E\{\kappa\} \bar{v}_M$ and $\bar{v}_\mu = E\{\kappa\} \bar{v}_\mu$. The mean values $\bar{v}_M$ and $\bar{v}_\mu$ were defined earlier; and $\kappa = \rho_1/\rho_2$, where ρ_1 and ρ_2 are i.i.d. Gamma random variables with unit mean and L_p degrees of freedom. In other words, ρ_1 represents either ρ_{Mi} or $\rho_{\mu i}$, and ρ_2 represents the other. For a uniform channel with L_p paths, the probability density of ρ (and therefore of ρ_1 or ρ_2) is

$$f_\rho(x) = \frac{L_p}{(L_p - 1)!} (x L_p)^{L_p - 1} e^{-x L_p}, \quad x > 0. \quad (19)$$

We can compute the mean of κ as $E\{\kappa\} = E\{\rho_1\} \cdot E\{\rho_2^{-1}\}$, where $E\{\rho_1\} = 1$ and

$$\begin{aligned} E\left\{\frac{1}{\rho_2}\right\} &= \frac{L_p}{L_p - 1} \int_0^\infty \frac{1}{(L_p - 2)!} y^{L_p - 2} e^{-y} dy \quad (20) \\ &= \frac{L_p}{L_p - 1}, \quad L_p > 1. \quad (21) \end{aligned}$$

We can therefore relate N_u to L_p , as follows:

$$N_u(L_p) = \frac{2K}{1 + \frac{L_p}{L_p - 1} \sqrt{\bar{v}_M \bar{v}_\mu}}. \quad (22)$$

Clearly, this approximation breaks down as L_p approaches 1, as it predicts zero capacity in that case.⁵ For $L_p > 1$, we obtain a simple relationship between user capacity and the degree of multipath dispersion. As L_p becomes infinite, user capacity converges to the estimate given by (5).

b) *Estimated User Capacity in a Non-Uniform Channel*:

The result in (22) can be used to approximate user capacity for *any* delay profile. Consider a channel delay profile having some arbitrary variation of $E\{r_n\}$ with n over the L_p paths. We can compute a *diversity factor*, DF , defined as the ratio of the square of the mean to the variance of ρ in (15). For independent Rayleigh paths, DF can be shown to be [14]

$$DF = \frac{\left(\sum_{n=1}^{L_p} E\{r_n\}\right)^2}{\sum_{n=1}^{L_p} (E\{r_n\})^2}. \quad (23)$$

From this definition, we see that the diversity factor for a uniform channel is precisely L_p .⁶ The proposed approximation makes use of this fact by first calculating the diversity factor for a given (non-uniform) channel. The approximate user capacity is then the value of N_u corresponding to $L_p = DF$, i.e., $N_u(DF)$ in (22).

4) *Total User Capacity with Finite Terminal Power*: To approximate user capacity under both finite dispersion and finite terminal power, we incorporate the approximations of Sections III and IV-A.3. We begin by first studying the uniform delay profile and then develop an approximation for a general non-uniform environment.

a) *Estimated User Capacity in a Uniform Channel*: As in Section III, we seek the largest N such that the probability of outage is α_{out} or lower. In calculating outage, we use the expressions in (6) and (11) but replace p_M and p_μ with p'_M and p'_μ , respectively, so that

$$p'_M = \Pr[E\{S'_M\}/\rho \tilde{T}'_M \leq FH]; \quad (24)$$

$$p'_\mu = \Pr[E\{S'_\mu\}/\rho \tilde{T}'_\mu \leq F], \quad (25)$$

where $E\{S'_M\} = E\{S_M\}/\eta W$, $E\{S'_\mu\} = E\{S_\mu\}/\eta W$, and ρ is a random variable with density given in (19). The steps used to compute $E\{S'_M\}$ and $E\{S'_\mu\}$ are identical to the steps outlined in Section III for the calculations of $E\{\tilde{S}'_M\}$ and $E\{\tilde{S}'_\mu\}$. The difference here is that the densities of S'_M and S'_μ depend on the densities of I_M and I_μ , (3), which account for variable fading, whereas $\tilde{S}'_M$ and $\tilde{S}'_\mu$ were obtained using the cross-tier interference terms in infinitely-dispersive channels. The densities of I_M and I_μ depend on the densities of the individual terms in their sums. The terms in each sum are i.i.d. random variates, denoted here by v_M and v_μ .

⁵The true capacity for a single-path Rayleigh fading channel is in fact quite poor, though not zero.

⁶Furthermore, via a simple implementation of the Schwarz inequality, it can be shown that the diversity factor for a non-uniform channel with L_p paths is less than L_p .

For a uniform channel with L_p paths, we note that $v_M = \kappa \tilde{v}_M$, where $\kappa = \rho_1/\rho_2$, and ρ_l ($l \in \{1, 2\}$) has probability density given in (19). Thus, the density of v_j ($j \in \{M, \mu\}$) can be computed as

$$f_{v_j}(v) = \int_0^\infty f_{\tilde{v}_j}(v/x) \cdot f_\kappa(x) dx, \quad v_j \in \{M, \mu\}, \quad (26)$$

where the probability density of $\tilde{v}_j$ is given in [4] and

$$f_\kappa(x) = \frac{1}{(L_p - 1)!} \sum_{i=0}^{L_p-1} \frac{(L_p - 1 + i)!}{i!} \cdot \frac{x^{i-1}(L_p x - i)}{(x + 1)^{L_p+1+i}}. \quad (27)$$

We obtain $f_\kappa(x)$ from its CDF, which can be computed as⁷

$$F_\kappa(x) = \mathbb{P}[\kappa \leq x] = \mathbb{P}[\rho_1 \leq \rho_2 x] \quad (28)$$

$$= 1 - \frac{1}{(L_p - 1)!} \sum_{i=0}^{L_p-1} \frac{x^i}{i!} \cdot \frac{(L_p - 1 + i)!}{(x + 1)^{L_p+1+i}}. \quad (29)$$

With the density of v_M and v_μ at hand, we use the analysis in [4] to compute the densities of I_M and I_μ for a given value of N . We then use the densities of these cross-tier interferences to compute the densities of S'_M and S'_μ , which in turn give us the mean values needed in (25). The outage probability for this capacity N is then determined using (6) and (11) with the substitutions for p_M and p_μ indicated in (25). Finally, we can approximate the maximum number of users supported for a desired outage level (α_{out}) for the uniform multipath channel.

b) Estimated User Capacity in a Non-Uniform Channel:

Given a non-uniform channel, we propose an approximation to user capacity for a given value of F that uses the above technique for the uniform channel. Specifically, we use the results of Section IV-A.3 to claim that a system in a non-uniform channel with diversity factor DF supports roughly the same number of users as the same system in a uniform channel with DF paths. Thus, for a given non-uniform delay profile, we first compute DF from (23). We then set L_p as the integer closest to DF and use the analysis above to estimate the total user capacity with outage α_{out} in a uniform channel with L_p paths. This value approximates user capacity in the given non-uniform channel.

B. Numerical Results

We use the two-cell system described in Figure 1 and Table 1 to obtain simulation results for finitely-dispersive channels. For a given configuration of N users, i.e., a fixed set of user locations and shadow fading, we generate 1000 values of ρ_M and ρ_μ for each user (based on the given channel delay profile) and record the instances of outage. We then calculate this outage measurement over 999 other random user locations and shadow fading (assuming a fixed value of N). The total instances of outage over all these trials determine the probability of outage for N .

Using this simulation method, we first calculate the

⁷We use the following to compute the CDF of κ : $\int_0^c \frac{x^m}{m!} e^{-x} dx = 1 - e^{-c} \sum_{i=0}^m \frac{c^i}{i!}$ and $\int_0^\infty x^n e^{-\alpha x} dx = n!/\alpha^{n+1}$.




Fig. 4. Total user capacity as a function of L_p , using both simulation and analytical approximation. Simulation results are also given for RA, HT, and TU channels, each at a value of L_p equal to the channel's diversity factor. (Two-cell two-tier system with unlimited terminal power)

user capacity with 5% outage probability when there are no transmit power constraints ($F = \infty$).⁸ This is done for the uniform channel and the RA, HT, and TU environments. For the uniform channel, we determine user capacity as a function of L_p ; Figure 4 shows results for both the simulation and approximation methods. The approximation curve follows the simulation curve closely, especially for smaller values of L_p . Figure 4 also shows the infinite- F capacity for the RA, HT, and TU environments (from simulation). We show each of these capacities at a value of L_p equal to its diversity factor. The diversity factors for the RA, HT, and TU environments are 1.6, 3.3, and 4.0, respectively. We see that, using the diversity factor, the capacity of a non-uniform channel can be mapped to the computed curve for the uniform channel, yielding a simple and reliable analytical approximation to user capacity. For channels with $DF > 5$, the total user capacity appears to be within 5% of that for an infinitely dispersive channel.

We also obtained user capacity (with 5% outage probability) as a function of F for the 2-path and 4-path uniform channels. This was done via both simulation and analytical approximation, and the results are presented in Figure 5. We observe, first, that the approximation matches the simulation results for the 2-path and 4-path channels in the region of interest, i.e., for $N \geq K$. Overall, the approximations improve as L_p increases. Furthermore, the user capacities noticeably decrease for $F < F^*$, where $F^* \approx 1$ for all three channels studied here, a result which is consistent with the infinitely-dispersive case (Figure 2).

In Figure 6, we plot user capacity versus F using the approximation method of Section IV-A.4 for $L_p = 2, 3$,

⁸For F large, 5% outage is the same as 5% infeasibility.




Fig. 5. Total user capacity for two uniform channels and the infinitely dispersive channel as a function of F , using both simulation and analytical approximation. (Two-cell two-tier system)




Fig. 6. Total user capacity for RA, HT, TU, and infinitely dispersive channels as a function of F , using both simulation and analytical approximation. (Two-cell two-tier system)

and 4 and simulation results for the RA, HT, and TU environments. The RA results closely match those for $L_p = 2$; the HT results closely match those for $L_p = 3$; and the TU results closely match those for $L_p = 4$. Thus, the diversity factor method of Section IV-A.4 allows us to reliably estimate user capacity versus F for any realistic delay profile.

Finally, we note that as in Figure 5, the critical value F^* is around 1 for all cases in Figure 6. Thus, we find that, regardless of the delay profile, $F^* \approx 1$. For the remainder of the paper, we assume practical values of $P_{\max}$ and $d_{\max}$ such that $F > 1$.

V. USER CAPACITY WITH VARIABLE FADING: MULTICELL SYSTEMS

A. Estimated User Capacity in Infinitely-Dispersive Channels

In computing the approximate user capacity in an infinitely dispersive channel, we use a result in [5] which states that maximal user capacity results when each cell in a multicell system supports an equal number of users. Let us denote N_p as the (equal) number of users supported in each cell and $N_\infty(L, M)$ as the total number of users supported in a system with L microcells, M macrocells, and an infinitely dispersive channel.⁹ We assume initially that all L microcells are embedded within one of the M macrocells (macrocell 1) and that the remaining $M - 1$ macrocells surround this macrocell. We first write $L + M$ inequalities representing the minimum SINR requirements at the $L + M$ bases. The received SINR's are determined using average interference terms. For example, the SINR requirement at macrocell base station 1 (which contains embedded microcells) is

$$\frac{\frac{W}{R} S_{M1}}{N'_p S_{M1} + \sum_{l=1}^L S_{\mu l} N_p \tilde{v}_M + \sum_{k=2}^M S_{Mk} N_p \tilde{v}_{MM} + \eta W} \geq \Gamma, \quad (30)$$

where $N'_p = N_p - 1$, S_{Mj} is the required received power at macrocell j , $N_p = N(L, M)/(L + M)$ (as per the optimal equal distribution of users), and the same-tier interference between macrocells is represented by its average value, i.e., $N_p \tilde{v}_{MM}$, which we assume to be the same for all macrocells. Here $\tilde{v}_{MM}$ is the interference into a macrocell caused by a user communicating with a neighboring macrocell, averaged over all possible user locations in $\mathcal{R}$ and over shadow fading. In our calculations, we simplify the SINR requirement in (30) by assuming that $\tilde{v}_{MM} \approx \tilde{v}_M$, i.e., interference due to two users in neighboring macrocells is roughly equal to the interference at a macrocell due to an embedded microcell user. Although macrocells transmit at higher powers than microcells, they are further apart from each other than is a macrocell base from an embedded microcell user. This approximation assumes that the larger distance between macrocells balances the impact of higher transmit powers.

Next, we determine the SINR requirement at macrocell j ($j \geq 2$). To do so, we assume (as above) that $\tilde{v}_{MM} \approx \tilde{v}_M$. We further assume that the interference from neighboring macrocells is much larger than the interference caused by transmissions in a few isolated microcells in a nearby macrocell, i.e., $\sum_{k \neq j} S_{Mk} \tilde{v}_{MM} N_p \gg \sum_{l=1}^L S_{\mu l} \tilde{v}_{M\mu} N_p$, where $\tilde{v}_{M\mu}$ is the interference at any macrocell base due to a microcell user embedded in a neighboring macrocell averaged over all possible user locations and shadow fading. Under these two assumptions, the SINR requirement at macrocell j ($j \geq 2$) is approximately

$$\frac{\frac{W}{R} S_{Mj}}{N'_p S_{Mj} + \sum_{k \neq j} S_{Mk} N_p \tilde{v}_M + \eta W} \geq \Gamma. \quad (31)$$

Finally, we calculate the SINR requirements at the L microcell bases. Here, we assume first that $\tilde{v}_{\mu M} \approx \tilde{v}_\mu$, where $\tilde{v}_{\mu M}$

⁹Note that $N_\infty(L, M) = (L + M)N_p$.

represents the interference into any microcell base due to a user in a neighboring macrocell averaged over user location and shadow fading. In other words, we assume the interference at a microcell from neighboring macrocells is comparable to interference caused by transmission to the umbrella macrocell. Note that this is a somewhat pessimistic assumption as $\tilde{v}_{\mu M}$ will typically be less than $\tilde{v}_\mu$. This pessimistic approach is balanced by assuming further that the microcell-to-microcell interference $\tilde{v}_{\mu\mu}$ is negligible. Here $\tilde{v}_{\mu\mu}$ is the average interference into any microcell base due to a user communicating with any other microcell. Thus, the required SINR equation at microcell l is

$$\frac{\frac{W}{R} S_{\mu l}}{N'_p S_{\mu l} + S_{M1} N_p \tilde{v}_\mu + \sum_{k=2}^M S_{Mk} N_p \tilde{v}_\mu + \eta W} \geq \Gamma. \quad (32)$$

These $L+M$ inequalities can be used to show [6] that $S_{Mj} \geq 0$ and $S_{\mu l} \geq 0$ for all $j \in \{1, 2, \dots, M\}$ and $l \in \{1, 2, \dots, L\}$ if and only if

$$N_\infty(L, M) = (L+M)N_p \leq \frac{K(L+M)}{1 + \sqrt{(L+M-1)\tilde{v}_M \tilde{v}_\mu}}. \quad (33)$$

A benefit of this simplified capacity condition is that it allows for capacity calculation using $\tilde{v}_M$ and $\tilde{v}_\mu$ alone. As a result, it is no more complex to determine than is N_T , the user capacity when $M=1$ and $L=1$, Section 2. Further, as the product $\tilde{v}_M \tilde{v}_\mu$ is robust to variations in propagation parameters and user distributions, so is the approximation in (33). Despite its simplified form, this approximation yields a fairly accurate estimate to the attainable user capacity.

A simple extension of the capacity expression in (33) can now be used to find the user capacity in a *general* multicell system, i.e., a system in which the L microcells can be embedded anywhere within the coverage areas of the M macrocells. We first note that, in the general system, each macrocell contains *on average* L/M microcells. Next, we use (33) to determine the user capacity for a multicell system in which there are M macrocells but only the center macrocell contains L/M microcells. In this case, each cell contains, N_p users, where

$$N_p = \frac{K}{1 + \sqrt{(\frac{L}{M} + M - 1)\tilde{v}_M \tilde{v}_\mu}}. \quad (34)$$

Next, we assume that this value of N_p hardly changes when some other macrocell contains (on average) L/M embedded microcells. Thus, we can finally approximate the total attainable capacity for the general multicell system as $(L+M)$ times the result in (34), i.e.,

$$N_\infty(L, M) \approx \frac{K(L+M)}{1 + \sqrt{(\frac{L}{M} + M - 1)\tilde{v}_M \tilde{v}_\mu}}. \quad (35)$$

B. Estimated User Capacity with Variable Fading

The goal here is to develop a calculation for the multicell user capacity in *finitely dispersive channels* which is as straightforward to calculate as the capacity expression in (35).

Although there are several approaches to this problem, we propose an extremely simple and highly accurate approximation method. First, we compute the diversity factor for the given multipath channel. Next, we make the assumption that systems with the same diversity factor support equivalent numbers of users and we seek to find $N_{DF}(L, M)$, the user capacity in a system with L microcells, M macrocells, and a multipath channel with diversity factor DF . We then use the results of Section IV to compute the total user capacity for a two-cell system, i.e.,

$$N_{DF}(1, 1) = \frac{2K}{1 + \frac{DF}{DF-1} \sqrt{\tilde{v}_M \tilde{v}_\mu}}. \quad (36)$$

We also compute the total user capacity for a two-cell system with infinite dispersion, i.e.,

$$N_\infty(1, 1) = \frac{2K}{1 + \sqrt{\tilde{v}_M \tilde{v}_\mu}}. \quad (37)$$

We use these two capacities to determine the capacity percentage loss due to dispersion, $p_{loss}(DF)$, for the two-cell system. This loss is given as

$$p_{loss} = \frac{N_{DF}(1, 1)}{N_\infty(1, 1)} = \frac{1 + \sqrt{\tilde{v}_M \tilde{v}_\mu}}{1 + \frac{DF}{DF-1} \sqrt{\tilde{v}_M \tilde{v}_\mu}}. \quad (38)$$

Finally, we claim and demonstrate through extensive numerical results that the total attainable user capacity in a multicell system with L microcells, M macrocells, and finite dispersion DF is simply $p_{loss}(DF)$ times the total attainable user capacity of a system with L microcells, M macrocells, and infinite dispersion, i.e.,

$$N_{DF}(L, M) \approx p_{loss}(DF) \cdot N_\infty(L, M) \quad (39)$$

$$= \frac{1 + \sqrt{\tilde{v}_M \tilde{v}_\mu}}{1 + \frac{DF}{DF-1} \sqrt{\tilde{v}_M \tilde{v}_\mu}} \cdot \frac{K(L+M)}{1 + \sqrt{(\frac{L}{M} + M - 1)\tilde{v}_M \tilde{v}_\mu}}. \quad (40)$$

C. Numerical Results

1) *Single-Macrocell/Multiple-Microcell System*: We begin with a large square region having side S and a macrocell base at its center. A fraction of the total system users are uniformly distributed over this region. This larger square is divided into n^2 squares with side s , as shown in Figure 7 for $n=5$. The smaller squares represent potential high-density regions. In each simulation trial, we randomly select L high density regions (excluding the center square which contains the macrocell base) and place a microcell base at the center. Finally, we assume that the L microcells have identical values for b_μ , H_μ , and σ_μ .

Our simulations assume $n=5$, meaning 24 possible candidate high density regions and the parameters in Table 1. For a given value of L , the simulation randomly selects L of the 24 high density regions. A portion of the total user population is uniformly-distributed over the large square region and the remaining users are uniformly distributed over the selected high density regions. The average fraction of the total user population placed in each region is $\frac{1}{L+1}$. As before, this was done to ensure that maximal user capacity occurs




Fig. 7. An example of the single-macrocell/multiple-microcell system, with $n = 5$.

with high probability [5]-[6]. The simulation then determines the total number of users supported with 5% outage. This is done for 23 other random selections of L high density regions, and the average over these selections is computed as a function of L .

We performed the above simulations for uniform channels with $L_p = 2$ and $L_p = 4$, and for the infinitely dispersive channel. The results are in Figure 8. In addition, we show the attainable user capacities predicted by (35) and (40). The simulation points match the corresponding approximations very tightly up to about $L = 12$, corresponding to a microcell *fill factor* (the fraction of macrocellular area served by microcells) of about one half. In other words, our approximation technique works reliably in the domain *hotspot* microcells.

2) *Multiple-Macrocell/Multiple-Microcell System*: We simulated a multiple-macrocell/multiple-microcell system by extending the system studied above. Specifically (Figure 9), there are m^2 macrocells and $m^2(n^2 - 1)$ candidate high density regions (locations for microcell bases). We randomly select L high density regions from this pool. We again accrue the average total capacity and its one-standard-deviation spread for the two extreme cases of dispersion, i.e., infinite dispersion and $L_p = 2$. The results for $m = 3$, $n = 5$ are in Figure 10. Also shown are the capacities predicted by (35) and (40) for $M = 9$ and $DF = 2$. The approximations closely match simulation points up to at least $L = 72$, which translates to roughly eight microcells per macrocell (fill factor of about one third). Thus, the approximation method is reliable in the domain of hotspot microcells.

VI. CONCLUSION

We first examined the effect of transmit power constraints and cell size on the uplink performance of a two-cell two-tier




Fig. 8. Total user capacity as a function of L for the 2-path and 4-path uniform channels and the infinitely dispersive channel using both simulation and analytical approximation. Although not shown here, the density of user capacity obtained from simulation is fairly tight about the reported mean value. (Unlimited terminal power)




Fig. 9. An example of the multiple-macrocell/multiple-microcell system, with $m = 3$ and $n = 5$.

CDMA system. We then investigated the effect of finite channel dispersion (which causes variable fading of the output signal power) on this capacity. Analysis was presented to approximate the uplink capacity of *any* channel delay profile using the uniform multipath channel, both with and without terminal power constraints. Finally, we presented an approximation to the uplink user capacity in larger multicell systems with finite dispersion and demonstrated its accuracy using extensive simulation.

While a particular set of system parameters was used in obtaining our numerical results, the analytical approximation




Fig. 10. Total user capacity as a function of L for the 2-path uniform channel and the infinitely dispersive channel using both simulation and analytical approximation. The error bars show the standard deviation spread about the mean. (Unlimited terminal power)

methods, and their confirmation via simulations, are quite general. What we have shown here, first, is that two-tier uplink user capacity can be reliably estimated in a two-cell system for arbitrary pole capacity, channel delay profile, shadow fading variances, transmit power limit, and cell size. Moreover, under realistic conditions on transmit power and cell size ($F > 1$), the method can be extended to the case of multiple macrocells with multiple microcells. Thus, we have developed simple, general and accurate approximation methods for treating a long-standing problem in two-tier CDMA systems.

ACKNOWLEDGMENT

We thank the editor, Dr. Halim Yanikomeroglu, for his helpful suggestions on expanding the scope of our study.

REFERENCES

- [1] J. Shapira, "Microcell engineering in cdma cellular networks," *IEEE Trans. Vehic. Technol.*, vol. 43, no. 4, pp. 817–825; Nov. 1994.
- [2] J.S. Wu, et al., "Performance study for a microcell hot spot embedded in cdma macrocell systems," *IEEE Trans. on Vehic. Technol.*, vol. 48, no. 1, pp. 47–59; Jan. 1999.
- [3] J. J. Gaytán and D. Mu noz Rodríguez, "Analysis of capacity gain and ber performance for cdma systems with desensitized embedded microcells," in *Proc. of International Conf. on Universal Personal Commun.* '98, 1998, vol. 2, pp. 887–891; Oct. 1998.
- [4] S. Kishore, et al., "Uplink capacity in a cdma macrocell with a hotspot microcell: exact and approximate analyses," *IEEE Trans. on Wireless Comm.*, vol. 2, no. 2, pp. 364–374; Mar. 2003.
- [5] S. Kishore, et al., "Uplink user capacity of a multi-cell cdma system with hotspot microcells," in *Proc. of Vehic. Techn. Conf. S-02*, vol. 2, pp. 992–996; May 2002.
- [6] S. Kishore, et al., "Uplink user capacity of multi-cell cdma system with hotspot microcells," submitted to *IEEE Trans. on Wireless Comm.*, Sept. 2003, <http://www.eecs.lehigh.edu/~skishore/research/inprogress.htm>.
- [7] S. Kishore, et al., "Uplink user capacity in a cdma macrocell with a hotspot microcell: Effects of finite power constraints and channel dispersion," in *Proc. of IEEE Globecom*, vol. 3, pp. 1558–1562, Dec. 2003.

- [8] S. Kishore, et al., "Downlink user capacity in a cdma macrocell with a hotspot microcell," in *Proc. of IEEE Globecom*, vol. 3, pp. 1573–1577, Dec. 2003.
- [9] K. S. Gilhousen, et al., "On the capacity of a cellular cdma system," *IEEE Trans. on Vehic. Technol.*, vol. 40, no. 2, pp. 303–312; May 1991.
- [10] V. Erceg, et al., "An empirically based path loss model for wireless channels in suburban environments," *IEEE J. on Sel. Areas in Comm.*, vol. 17, no. 7, pp. 1205–1211; July 1999.
- [11] T. S. Rappaport, *Wireless Communications: Principles and Practice*, Prentice Hall, 1996; Chapter 3.
- [12] S. Kishore, *Capacity and Coverage in Two-tier Cellular CDMA Networks*, Ph.D. Thesis, Department of Electrical Engineering, Princeton University; Jan. 2003.
- [13] "Deployment Aspects," 3GPP Specifications, TR 25.943 V4.0.0, (2001–2006), 2001.
- [14] A. Awoniyi, et al., "Characterizing the orthogonality factor in wcdma downlink," *IEEE Trans. on Wireless Comm.*, vol. 2, no. 4, pp. 611–615; July 2003.

W/R	128	h_m	1.5 m
Γ_M	7 dB	Γ_μ	7 dB
h_M	60 m	h_μ	9 m
b_M	100 m	b_μ	100 m
H_M	$10H_\mu$	D	300 m
σ_M	8 dB	σ_μ	4 dB
s	200 m	S	1 km

TABLE I

SYSTEM PARAMETERS USED IN SIMULATION.



Shaline Kishore received the B.S. and M.S. degrees in Electrical Engineering from Rutgers University in 1996 and 1999, respectively, and the M.A. and Ph.D. degrees in Electrical Engineering from Princeton University in 2000 and 2003, respectively.

Dr. Kishore is an Assistant Professor in the Department of Electrical and Computer Engineering at Lehigh University. From 1994 to 2002, she has held numerous internships and consulting positions at AT&T, Bell Labs, and AT&T Labs-Research. She is the recipient of the National Science Foundation CAREER Award, the P.C. Rossin Assistant Professorship, and the AT&T Labs Fellowship Award. Her research interests are in the areas of communication theory, networks, and signal processing, with emphasis on wireless systems.



Larry Greenstein (M'59-SM'80-F'87-LF'02) received the B.S., M.S., and Ph.D. degrees in Electrical Engineering from Illinois Institute of Technology, Chicago, in 1958, 1961, and 1967, respectively.

From 1958 to 1970, he was with IIT-Research Institute, Chicago, IL, working on radio-frequency interference and anti-clutter airborne radar. He joined Bell Laboratories, Holmdel, NJ, in 1970. Over a 32-year AT&T career, he conducted research in digital satellites, point-to-point digital radio, light-wave transmission techniques, and wireless communications.

For 21 years during that period (1979-2000), he led a research department renowned for its contributions in these fields. His research interests in wireless communications have included measurement-based channel modeling, microcell system design and analysis, diversity and equalization techniques, and system performance analysis and optimization. Since April 2002 he has been a research professor at Rutgers WINLAB, Piscataway, NJ, working in the areas of ultra-wideband systems, sensor networks, relay networks and channel modeling. Dr. Greenstein is an AT&T Fellow and a member-at-large of the IEEE Communications Society Board of Governors. He has been a guest editor, senior editor and editorial board member for numerous publications.



H. Vincent Poor (S'72, M'77, SM'82, F'97) received the Ph.D. degree in EECS from Princeton University in 1977. From 1977 until 1990, he was on the faculty of the University of Illinois at Urbana-Champaign. Since 1990 he has been on the faculty at Princeton, where is the George Van Ness Lothrop Professor in Engineering. Dr. Poor's research interests are in the area of statistical signal processing and its applications in wireless networks and related fields. Among his publications in these areas is the recent book *Wireless Networks: Multiuser Detection in Cross-*

Layer Design (Springer: New York, NY, 2005).

Dr. Poor is a member of the National Academy of Engineering, and is a Fellow of the Institute of Mathematical Statistics, the Optical Society of America, and other organizations. In 1990, he served as President of the IEEE Information Theory Society, and in 1991-92 he was a member of the IEEE Board of Directors. He is currently serving as the Editor-in-Chief of the *IEEE Transactions on Information Theory*. Recent recognition of his work includes the Joint Paper Award of the IEEE Communications and Information Theory Societies (2001), the NSF Director's Award for Distinguished Teaching Scholars (2002), a Guggenheim Fellowship (2002-2003), and the IEEE Education Medal (2005).



Stuart Schwartz received the B.S. and M.S. degrees from M.I.T. in 1961 and the Ph.D. from the University of Michigan in 1966. While at M.I.T. he was associated with the Naval Supersonic Laboratory and the Instrumentation Laboratory (now the Draper Laboratories). During the year 1961-62 he was at the Jet Propulsion Laboratory in Pasadena, California, working on problems in orbit estimation and telemetry. During the academic year 1980-81, he was a member of the technical staff at the Radio Research Laboratory, Bell Telephone Laboratories, Crawford Hill, NJ, working in the area of mobile telephony.

He is currently a Professor of Electrical Engineering at Princeton University. He was chair of the department during the period 1985-1994, and served as Associate Dean for the School of Engineering during the period July 1977-June 1980. During the academic year 1972-73, he was a John S. Guggenheim Fellow and Visiting Associate Professor at the department of Electrical Engineering, Technion, Haifa, Israel. He has also held visiting academic appointments at Dartmouth, University of California, Berkeley, and the Image Sciences Laboratory, ETH, Zurich. His principal research interests are in statistical communication theory, signal and image processing